

EagleTac M2 Models – M2C4 / M2XC4 Specifications

11W Compact Hand-Held Tactical Flashlight

Highest EagleTac Model Signature

- Type III Hard Anodized Aluminum Construction
- Constant Current Regulation Output C2800 Light Engine
- All-in-One Digital Rotary Switch with Off Position and Tactical Strobe
- Rotary Switch made in Re-enforced Polycarbonate with Smooth Rubber Coating
- Efficient Dual Slot Loaded Battery Tray System, Re-enforced by Anodized Aluminum Constructions and Stainless Steel Mounting Screws. Two Custom Fitment Setting for CR123A and 18650. Printed Battery Orientation Diagram
- Custom Fitting Silicon o-rings and Rubber o-rings for IPX-8 Waterproof Standard
- Gold Plated Copper Contacts for Superior Conductivity and Durability
- Type III Hard Anodized Aluminum Tail-Cap with Tail-Standing and Lanyard Attachment Ability (Clicky version has been cancelled)
- Ultimate LED and Driver Components Thermal Treatment for Continuous High Output
- Syntax I Anti-Reflector Coated and Harden Shock Mounted Window
- Removable Smooth Crenated Stainless Steel Bezel
- Tail and Body parts are Secured by Black-out Stainless Steel Mounting Screws

Operations:

- Brightness Level: Strobe -> 100% <-> 40% <-> 3.5 % <-> Off
- M2 Output Level : Strobe< -> 900 lumen <-> 420 lumen <-> 170 lumen <-> 45 lumen <-> Off
- M2X Output Level (Cool White): Strobe< -> 800 lumen <-> 360 lumen <-> 150 lumen <-> 40 lumen <-> Off
- M2X Output Level (Neutral White): Strobe< -> 665 lumen <-> 300 lumen <-> 125 lumen <-> 33 lumen <-> Off
- Runtime (4x123A): Strobe <-> 1.2hr <-> 3.5hr <-> 9.5 hr <-> 45hr <-> Off
- Runtime (2x18650): Strobe <-> 1.5hr <-> 4.5hr <-> 12.5 hr <-> 55hr <-> Off

M2C4 – Monster Flood light w/ medium throw performance

- 900 LED lumen constant brightness output*
- Quad-die P7 D-bin Premium tint LED Emitter
- ET54 Aluminum Optical Reflector in Orange Peel finish

M2XC4 – Monster Throw light w/ medium flood performance

- 800 LED lumen constant brightness output
- Available in:
 - 1) Triple CREE R2 XR-E Cool White LED Emitter
 - 2) Triple CREE Q3 XR-E Neutral White LED Emitter
- Tri-ET28 Aluminum Optical Reflector in Smooth finish

Included accessories:

- Paracord lanyard with position lock
- Rigid Nylon holster with adjustable mounting for different belt sizes
- Spare oring

Optional accessories:

- Filter kit (Red/Blue/Green/IR), diffuser kit, window protector cap
- M25 Clicky replacement kit, includes M25 clicky module, clicky tail-cap made in re-enforced polycarbonate with smooth rubber coating, silicon tail-boot, retainer ring, spare stainless steel mounting screws, installation manual
- 123A battery magazine holder, efficiently load 123A lithium batteries, compatible with M2 battery tray
- M2 additional battery tray, two custom fitment for 18650 and 123A batteries, gold plated copper contacts

*Seoul Semiconductor rated D-Bin P7 LED with 800-900 lumen @2.8A
LED lumen is measured at LED.